

3" RolaCage User Guide

Introduction

The RolaCage allows 3" diameter masts of up to 7m in height to be deployed smoothly and easily. The mast is inserted loose into the cage. The design does not need a central spindle. Deploy to the required length and lock the retaining plate using the wing screw. Ensure that:

1. About a metre is still left inside the cage
2. The base of the cage is secured with pegs
3. The RolaCage is securely locked with the central screw



Product Components

Component	RolaTube Part Number	NATO Stock Number	Qty	Material	Dimensions
RolaCage	800-007102	5885-99-397-9209	1	HDPE Aluminium	W326mm x D272mm x H270mm Weight 2.3kg
Pegs	207-002001	4030-99-160-7145	4		

Deploying the RolaTube

1. Remove the retaining pin that holds the top two bars in place



2. Slide out the top two bars



3. Insert the mast ensuring that it will exit through the larger gap between the bars, then reposition the top two bars and replace the retaining pins.



4. Unroll mast to the required length (ensuring 1m is kept in the RolaCage), then tighten the wing screw on the side as this applies the brake and keeps the mast in position.



Products have been designed and tested to be compliant with the relevant aspects of MIL-STD-810G

Disclaimer: The technical and operational information contained within this document relates only to the specific product referred to in this document and may not be applicable when such product is not used in accordance with such operational instructions. The Company reserves the right to change technical and operational information from time to time. A copy of the latest version is available on the Company's website: www.rolatube.com

A copy of the Company's terms and conditions of business are also included on the Company's website.

RTL Materials Ltd trading as RolaTube Technology
130 Wellworthy Road, Ampress Park
Lymington SO41 8JY, UK

t: +44 (0)1590 688019
e: enquiries@rolatube.com
www.rolatube.com

Registered in England & Wales
No. 3332020
VAT Reg 706 972 317

