



Model No. ARZ 204

Width : 4 Meter

Length : 5 Meter

Height side wall: 2 meter

Height at ridge: 2.70 meter

Packing size: approx. ca. 120 x 85 x 55 cm

Weight approx. : 80 kg

Frame

Completely inflatable, of airtight double-sided PVC coated polyester fabric [1,100 g/m²], fastened with Velcro closures to the tent skin and floor. Easy replacement of tent skin, floor and frame. The tents can be set up in 1.5 minutes using the compressed air kit. Depending on tent size, assembly takes 2-4 minutes when using an electric blower. A pressure relief valve prevents excessive pressure in the frame.

Tent skin

Tent skin: One-sided PU coated polyester fabric [240 g/m²]; flame retardant, waterproof and mildew resistant design

Floor

Floor covering of double-sided PVC coated polyester fabric [550 g/m²]

Other fittings

- ✂ 2 windows equipped with a mosquito net
- ✂ 2 fittings at the entrance for connecting additional tents to large unit
- ✂ Ventilation flaps in gable above entrance
- ✂ 4 Openings at the side for heating or cable equipment etc.
- ✂ 4 Opening at the gables (2 X each gable) for electrical cable
- ✂ Hangers on the frame to carry lamps or other equipment

LANCO

Dr. Lange GmbH & Co. KG

Sure Wisch 6, 30625 Hannover, Germany

- ✓ Quick and easy assembly and disassembly
- ✓ Modular design
- ✓ Multifunctional
- ✓ All tents interconnectable
- ✓ Reliable - Transportable
- ✓ Flame/UV resistant material
- ✓ Ready to use in minutes
- ✓ Ideal solution for all emergency situations
- ✓ Durable and robust construction
- ✓ Efficient deployment and use - any type of terrain or environment
- ✓ PVC-coated fabric, flame retardant and UV resistant

Accessories

- ✂ 1X Bag for Tent Skin
- ✂ 1X Bag for accessories
- ✂ 6X Guy ropes
- ✂ 10X T-Pegs
- ✂ 1X Hammer
- ✂ 1X Hand Pump
- ✂ 1X Electric Blower
- ✂ 1X Repair Kit
- ✂ 1X Manual and care Instructions